



THE #1 CHOICE OF  
PAINTING PROFESSIONALS®

## MATERIAL SAFETY DATA SHEET

### **MSDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS**

The following Material Safety Data Sheet (MSDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Dunn-Edwards Corporation; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following MSDS supersedes any previously issued MSDS for each product covered. The reader is advised to destroy any obsolete MSDS and refer only to this MSDS. As permitted by OSHA, each MSDS may apply to a class of products which have similar hazards and contents.

Products covered by this MSDS are listed below:

<b>ACHS10-0:</b> ACRI-HUES Flat	<b>SSHV10-0:</b> SPARTASHIELD VA Flat
<b>ACWL10-0:</b> ARCI-WALL Flat	<b>SWLL10-0:</b> SPARTAWALL Flat
<b>ENSO00-0:</b> ENSO Primer	<b>SWLL20-0:</b> SPARTAWALL Velvet
<b>ENSO10-0:</b> ENSO Flat	<b>SWLL30-0:</b> SPARTAWALL Eggshell
<b>ENSO30-0:</b> ENSO Eggshell	<b>SWLL40-0:</b> SPARTAWALL Low Sheen
<b>ENSO50-0:</b> ENSO Semi-Gloss	<b>SWLL50-0:</b> SPARTAWALL Semi-Gloss
<b>EVSH10-0:</b> EVERSIELD Flat	<b>UGPR00-1:</b> ULTRA-GRIP Premium
<b>EVSH20-0:</b> EVERSIELD Velvet	<b>UGSL00-0:</b> ULTRA-GRIP Select
<b>EVSH30-0:</b> EVERSIELD Eggshell	<b>ULDM00-0-GR:</b> ULTRASHIELD DTM Gray Primer
<b>EVSH30-2:</b> EVERSIELD Eggshell	<b>ULDM50-0:</b> ULTRASHIELD DTM Semi-Gloss Paint
<b>EVSH40-0:</b> EVERSIELD Low Sheen	<b>ULMS00-0-WH:</b> ULTRASHIELD Multi-Surface Primer
<b>EVSH40-2:</b> EVERSIELD Low-Sheen	<b>ULSH40-0:</b> ULTRASHIELD Low Sheen Paint
<b>EVSH50-0:</b> EVERSIELD Semi-Gloss	<b>ULSH60-0:</b> ULTRASHIELD Gloss Paint
<b>EVSH60-2:</b> EVERSIELD Gloss	<b>VNSL00-0:</b> VINYLASTIC Select
<b>EZPR00-1:</b> EZ-PRIME Premium	<b>W 360V:</b> ENDURASEAL
<b>PMCE10-0:</b> CONTRACTOR'S EDGE Flat	<b>W 370:</b> ENDURAWALL
<b>PMCE30-0:</b> CONTRACTOR'S EDGE Eggshell	<b>W 600:</b> ECOSHIELD Primer
<b>PMCE50-0:</b> CONTRACTOR'S EDGE Semi-Gloss	<b>W 601:</b> ECOSHIELD Flat
<b>SPMA10-0:</b> SUPREMA Flat	<b>W 602:</b> ECOSHIELD Low Sheen
<b>SPMA10-1:</b> SUPREMA Flat	<b>W 603:</b> ECOSHIELD Semi-Gloss
<b>SPMA20-0:</b> SUPREMA Velvet	<b>W 615:</b> ACOUSTIKOTE
<b>SPMA20-1:</b> SUPREMA Velvet	<b>W 5361:</b> Athletic Field Striping Paint
<b>SPMA30-0:</b> SUPREMA Eggshell	<b>W 6079:</b> AQUAFALL Flat
<b>SPMA40-0:</b> SUPREMA Low Sheen	<b>W 6240:</b> VERSAFLAT
<b>SPMA50-0:</b> SUPREMA Semi-Gloss	<b>W 6310:</b> DURA-TILT
<b>SSHL10-0:</b> SPARTASHIELD Flat	<b>W 6401V:</b> QUIK-WALL
<b>SSHL20-0:</b> SPARTASHIELD Velvet	<b>W 6402V:</b> SUPER-WALL
<b>SSHL30-0:</b> SPARTASHIELD Eggshell	<b>W 6403V:</b> SUPER-WALL Ready-To-Use



EMERGENCY AND FIRST AID PROCEDURES: If affected by inhalation of vapor, move victim to fresh air. If not breathing, apply artificial respiration and call emergency medical care. For eye contact, flush eyes with fresh water for at least 15 minutes. If irritation persists, seek medical attention. For skin contact, wash thoroughly with soap and water. Remove any contaminated clothing. If swallowed, have victim drink enough fresh water to ensure dilution. Call emergency medical care.

-----  
**SECTION VI - REACTIVITY DATA**  
-----

STABILITY: Stable. HAZARDOUS POLYMERIZATION: Will not occur.  
HAZARDOUS DECOMPOSITION PRODUCTS: Combustion can produce carbon monoxide and/or carbon dioxide.  
CONDITIONS TO AVOID: Avoid storage or use at temperatures below 40°F. Avoid freezing.  
INCOMPATIBILITY (MATERIALS TO AVOID): Avoid water-reactive materials, strong oxidizers, acids and alkalis.

-----  
**SECTION VII - PRECAUTIONS FOR SAFE HANDLING, STORAGE, AND DISPOSAL**  
-----

PRECAUTIONS FOR HANDLING AND STORAGE: Keep containers closed when not in use. Do not handle or store near heat, flame, or strong oxidizers, acids and alkalis. Store in cool, well-ventilated area. Rotate stock, use older material first. Inspect all containers for leaks.  
STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED: Dike and absorb spilled liquid with inert material such as clay granules, sand, earth, or sawdust. Use rags to clean up small amounts of spilled material.  
WASTE DISPOSAL METHOD: Collect contaminated absorbent material and rags into a suitable container and dispose in accordance with all applicable local, state, and federal regulations.

-----  
**SECTION VIII - CONTROL MEASURES FOR SAFE USE**  
-----

RESPIRATORY PROTECTION: For spray application, use particulate filter mask to avoid breathing spray mist. Exposed persons with unusual allergic sensitivity may need organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).  
VENTILATION: For interior use, general mechanical ventilation may be sufficient to disperse vapor. Otherwise, open doors and windows or use portable fans to provide local exhaust.  
EYE PROTECTION: Use safety glasses, goggles, or face shield to protect eyes.  
PROTECTIVE GLOVES: Use waterproof gloves (e.g., latex, vinyl, rubber, neoprene) to avoid skin contact.  
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Waterproof headcovering and general protective clothing are recommended for protection as necessary.  
WORK/HYGIENIC PRACTICES: Wash hands and face before eating.

-----  
**SECTION IX - SPECIAL CAUTIONS**  
-----

Do not store in areas subject to freezing temperatures. Keep above 40°F at all times. Use only with adequate ventilation or protection. Avoid breathing spray mist or vapor. Do not ingest. Avoid contact with skin. Close container after each use. Keep out of reach of children.

-----  
**SECTION X - TRANSPORTATION INFORMATION**  
-----

Shipping Requirements: Products covered by this MSDS are not subject to DOT, IATA/ICAO, or IMO/IMDG transportation regulations. Acceptable for air transport as non-hazardous goods.

\*\*\*\*\* DISCLAIMER \*\*\*\*\*

THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY DUNN-EDWARDS CORPORATION WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.